

## TRANSPORT AND STORAGE INSTRUCTIONS FOR GOODS PURCHASED FROM

## TRANSPORT

When picking up goods (the "Goods") purchased from Worthouse Inc, a Delaware corporation located at 321 Mills Rd, Waynesboro, GA 30830 with your own vehicle, such vehicle must be equipped with an appropriate loading platform that will enable you to freely load and unload the Goods. Note that properly fixed metal sheet packages during transport will prevent damages.

Metal sheets must be protected against moisture at all times.

It is advisable to unload the Goods in original packaging with the assistance of mechanical equipment, such as a forklift. It is recommended to unload Goods using a forklift truck with proper fork spacing secured so as to prevent any damages to the metal sheet surface (scratches, indents or breaks).

Manual unloading should be carried out by individuals capable of hauling heavy loads. Special attention must be given so that metal sheets are not moved against one another, or lateral edges of a metal sheet are not bent. Note that it is difficult to properly install metal sheets deformed during unloading and handling operations.

## STORAGE

Coated metal sheets in original packaging should be stored in dry and ventilated rooms. In case of storing packages for a longer period of time, remove the protective films and ensure free air circulation between sheets. The maximum storage time should not exceed 6 months from the production date, which is indicated on the package. Packages should be stored in one layer. The distance from the floor should be at least 8 inches. Pallets prepared for shipment by Worthouse cannot be repacked or stacked under any circumstances.

Be advised that the fact that the Goods are equipped with protective films does not release you from your obligation to properly secure metal sheets during storage.

## **CUTTING AND INSTALLATION**

To cut metal sheets, you must use a shearing machine or electric shears with a rotating head. Once the installation has been finished, the surface of the metal sheet must be thoroughly cleaned so that no impurities (metal impurities in particular) that may lead to paint and zinc layer damages (scratches, rust, perforation etc.) are left. In case of surface damage, make a required (spot) touch up using a paint compliant with the original color of the metal sheet.

No warranty claims shall be made in case of using a grinder.

NOTE: In case of surface damages of metal sheets resulting from moisture or mechanical damages, any possible claims will be rejected.